



3D VIEW

技术要求Technical requirement:

- 1.额定电压、电流Rated voltage/current: AC600V / 80A
- 2.耐压Rated withstand voltage: AC2500V
- 3.绝缘电阻Insulation resistance: 5000MΩ, 接触电阻Contact resistance: 1mΩ
- 4.使用温度Service temperature: -40℃~+105℃.

				设计design	批准approve	日期date	未注公差Undefined tol		设计design	—	—	 江西航同电气科技有限公司 Jiangxi Huntect Electrical Technology Co., Ltd.
—	—	—	—	—	—	—	0--10	±0.3	审核check	—	—	
—	—	—	—	—	—	—	>10--30	±0.5	批准approve	—	—	
—	—	—	—	—	—	—	>30--100	±1.0	材料material	—	—	
—	—	—	—	—	—	—	>100--250	±1.5	重量W.T. (g)	/	/	
—	—	—	—	—	—	—	>250	±1%	比例scale	1:3	名称 name	穿墙端子
版本rev.				标记mark	数量no.		未注角度Undefined angle ±2°		图幅size	A3	型号 spc.	RBH80A-5P BK
							未注尺寸Undefined size mm		第三视角	页码sheet /	料号 PN	/
									3rd angle projection	图号dwg No.	4001101219	