



技术要求technical requirement

- 1.使用环境温度working Ambient temperature: $-40^{\circ}\text{C}\sim+85^{\circ}\text{C}$
- 2.额定负载Rated load: 300VAC 10A
- 3.介质耐压Medium voltage resistance 线圈/coil/触点/contact: 2000 V/s; 触点间the contact space: 2000 V/s
- 4.螺钉扭矩Screw torque: 1.0 N.M
- 5.连接导线connecting lead: 20-14/0.5-2.5AWG/mm²

—	—	—		—	—	—
—	—	—		—	—	—
—	—	—		—	—	—
版本rev.	标记mark	处数no.		设计design	批准approve	日期date

未注公差undefined tol	设计design	—	—		江西航同电气科技有限公司	
0--10 0.3	审核check	—	—		Jiangxi Huntect Electrical Technology Co.,Ltd.	
>10--30 0.5	批准approve	—	—			
>30--100 1.0	材料material	/		名称 name	通用型功率继电器插座	
>100--250 1.5	重量W.T. (g)	/	比例scale	1:1	型号 spc.	General Purpose Power Relay Socket
>250 1%	第三视角		图幅size	—	图号 dwg No.	SRL-2E
未注角度公差undefined angle 2°	第三角投影	3rd angle projection	页码sheet	/	图号 dwg No.	—
未注尺寸公差undefined size mm						