

62.4

76

45.8

15.6

#### 技术要求technical requirement

- 1.额定负载电流、电压Rated load current, voltage:10A 300VAC
- 2.介质耐压线圈/触点Dielectric withstand voltage coils/contacts:4000V/S
- 3.介质耐压触点间Dielectric withstand pressure between contacts:2500VS
- 4.螺钉扭矩Screw torque:1.0N.m
- 5.外接连接导线External connecting leads:20-14/0.5-2.5AWG/mm<sup>2</sup>
- 6.使用环境operating environment:-40℃~+85℃

|        |        |       |
|--------|--------|-------|
| —      | —      | —     |
| —      | —      | —     |
| —      | —      | —     |
| 版本rev. | 标记mark | 处数no. |

设计design 批准approve 日期date

|                          |                      |                                                                                       |         |                                                                                       |                                                |               |
|--------------------------|----------------------|---------------------------------------------------------------------------------------|---------|---------------------------------------------------------------------------------------|------------------------------------------------|---------------|
| 未注公差undefined tol        | 设计design             | —                                                                                     | —       |  | 江西航同电气科技有限公司                                   |               |
| 0--10 0.3                | 审核check              | —                                                                                     | —       |                                                                                       | Jiangxi Huntect Electrical Technology Co.,Ltd. |               |
| >10--30 0.5              | 批准approve            | —                                                                                     | —       |                                                                                       |                                                |               |
| >30--100 1.0             | 材料material           | /                                                                                     |         |                                                                                       | 名称 name                                        | 插座<br>Sockets |
| >100--250 1.5            | 重量W.T. (g)           | /                                                                                     | 比例scale | 1:1                                                                                   |                                                |               |
| >250 1%                  | 第三视角                 |  | 图幅size  | —                                                                                     | 型号 spc.                                        | SRJ-2S        |
| 未注角度公差undefined angle 2° | 3rd angle projection | 页码sheet /                                                                             |         |                                                                                       | 图号dwg No.                                      | —             |
| 未注尺寸公差undefined size mm  |                      |                                                                                       |         |                                                                                       |                                                |               |